

## Sawn timber for all building requirements

PÖLKKYsawn-timber products are especially suitable both for the building industry and furniture/joinery industries as a raw material. You can recognize this high standard quality and special sawn timber from its dimensional accuracy and fine sawn surface quality. Nordic high-quality pine and spruce raw materials, modern production techniques and skilled professional personnel combine together to ensure a stable and high quality product with every delivery.

A characteristic of the Nordic wood is that it has a dense grain structure; proportionally large heartwood and smaller than average sized knots. This makes for the good woodworking characteristics and gives excellent strength qualities. High quality PÖLKKYsawn-products are sawn individually and accurately. The correct sawing process ensures that it reflects the best raw wood material qualities. After sawing, the sawn timber is dried in a modern kiln to the pre-defined humidity.

### Quality

U/S (US), Fifth (V), sawn product (SF), Furniture quality (POLA), Sixth (VI), waney timber (VII).

Selection is made according to Nordic sorting guidelines or to the customer's instruction.

**Std Sizes** o = pine, x = spruce

| Mm  | 50 | 75 | 100 | 125 | 150 | 175 | 200 | 225 |
|-----|----|----|-----|-----|-----|-----|-----|-----|
| 19  |    | o  | o   | o   | o   |     |     |     |
| 22  |    | x  | x   | x   | x   | x   | x   | x   |
| 25  |    | o  | o   | o   | o   | o   | o   | o   |
| 32  |    | ox | ox  | ox  | ox  |     |     |     |
| 36  |    | x  | x   | x   | x   |     |     |     |
| 38  |    | ox | ox  | ox  | ox  |     |     |     |
| 44  |    | x  | ox  | x   | ox  |     |     |     |
| 47  |    | x  | x   | x   | x   |     | 12  |     |
| 50  | o  | ox | ox  | ox  | ox  | ox  | 1   |     |
| 63  | o  | o  |     | ox  | ox  | ox  | ox  | ox  |
| 75  |    | o  |     | ox  | ox  | ox  | ox  | ox  |
| 100 |    |    |     |     | ox  | ox  | ox  | ox  |
| 125 |    |    |     |     | ox  | ox  | ox  | ox  |
| 150 |    |    |     |     | ox  | ox  | ox  | ox  |

Ask if needed for other dimensions, lengths and qualities!

### Lengths

Falling lengths 1,8 - 5,4 m, 30 or 10 cm modules.

Special batches precision cut by special order, tolerances of ± 2 mm.

### Humidity

Extra dry: 8 %, 10 %, 12 %. Plane planed dry: 16 %

Export dry: 18 %. Green.

### Special sawn cuts

Green split logs free of heart or heart-split.

### Manufacturer

Pölkky Oy, Kemijärventie 73, 93600 Kuusamo, FINLAND

Tel. +358 (0)20 764 0200 | office@polkky.fi



OFFICIAL WOOD SUPPLIER OF SANTA CLAUS

© SANTA CLAUS FOUNDATION™

